Ressol Chem

Nr. Meghmani Organics Ltd. Plot No. 4615, G.I.D.C. Ankleshwar – 393 002.

Manufacture & Supplier Of:

Synthetic Resin, Varnishes, Ph. No. (O) 02646 – 238145 (M) 94279 - 33680.

Product Name: Bestomine MF 610

Type: Synthetic Amino Resin – Butylated Melamine

Formaldehyde Resin.

Salient Features: MF 610 is Mix Butanol base Moderate reactive Melamine formaldehyde Resin with excellent hardness, reactivity and Good color retention.

Applications: Mainly used for high gloss general purpose stoving enamels. Used in D.G. lacquer for coating metallised polyester films and in clear stoving lacquers.

Solubility: Bestomine MF 610 is soluble in alcohols, esters, ketones, glycol ethers, aromatic hydrocarbons.

Specifications as follows:

1. Appearacne Colorless water white Liquid.

2. Colour: 1 Max. on Gardner Scale

3. Clearity: Clear

4. Viscosity: 60 ± 15 seconds. (By Ford Cup B 4 @ 30° C)

5. % of Non volatile: 55 ± 2 %

6. Acid Value: Max 1.00 mg Koh / gm resin.

7. Free Formalin: 2% Max.
8. M.T.T.: 200 - 400 %

9. X.T.T.: Infinite
10. Specific Gravity: 1.01 – 1.03

11. Electric Resistivity: 300 KOhms Maximum.

Remarks: Supplying contains 65 ± 2 % Solid @ 120° C for 2 hours and 12 poise to 22 poise viscosity.

Packing: 210 Kgs M.S. Barrel and 25 Kgs MS Drum.